

Cold Wave



Tube: Oil resistant, synthetic rubber

Reinforcement: Braids of high tensile steel wire
Multi spiral high tensile super flexible four wire

Cover: Oil and weather resistant synthetic rubber

Temperature: -76 degree F/+212F

Application: Petroleum based hydraulic fluid, gasoline, water, diesel fuels, lubricating oils, glycol, mineral oils, and more

Termination: 200 series & 400XF series

Features and Benefits:

- Extreme bend radius in low temperature
- Multipurpose hose, low and high temp
- Weather protectant cover

Part Number	Hose I.D.	Hose O.D.		Max Working Pressure	Minimum Burst Pressure	Minimum Bend Radius		Weight	Termination
	(in)	(in)	(mm)	(psi)	(psi)	(in)	(mm)	(lbs/ft)	Fitting Type
Coldwave-04	1/4"	.59	15.0	6,000	24,400	4.0	102	.24	200 Series
Coldwave-06	3/8"	.75	19.0	5,100	19,100	5.0	127	.36	200 Series
Coldwave-08	1/2"	.87	22.2	5,000	15,950	7.0	178	.46	200 Series
Coldwave-10	5/8"	1.00	25.4	4,000	14,500	8.0	203	.54	200 Series
Coldwave-12	3/4"	1.15	29.3	3,500	12,300	9.5	241	.63	200 Series
Coldwave-16	1"	1.50	38.0	2,500	9,400	12.0	305	.91	200 Series
Coldwave-20	1-1/4"	1.90	48.3	1,800	7,250	16.50	419	1.44	200 Series
Coldwave12-4W	3/4"	1.24	31.4	6,100	20,305	7	178	.96	400XF Series
Coldwave16-4W	1"	1.52	38.6	5,500	20,305	9	229	1.40	400XF Series
Coldwave20-4W	1-1/4"	1.78	45.1	4,800	20,305	12	305	2.55	400XF Series