

Other Products Offered

BOP Edition



Industrial Hose Edition




Clamp Edition

Clamp Edition


UHP Edition


Ultra High Pressure

Americas



Valve Edition







Color Safe System



DNP Americas Color Code Couplings

- Color coding can be utilized in a wide range of industrial markets when connecting and disconnecting is needed.
- Easy to use and implement
- Easy to see at a distance
- Helps to keep workers safe • Helps to prevent equipment damage
- Implements poka-yoke by establishing a mistake-proofing system

- BOP FSI Series





BOP Quick Couplings



BOP Quick Disconnects

- PVT4-BOP Series
- PVT4-SS-BOP Series
- FSI-BOP Series
- HNV-BOP Series
- VFF-HD-BOP Series
- * Red color on coupling and nipple designates that the coupings are B.O.P. fire approved.
- All BOP Coupling series are API 16D
- API 16D Certificate that states that all couplings must maintain pressure when exposed to 1300° F (700° C) for a 5 minute period.



Quick Disconnects Mail Valves Mail Clamps Mail Hose Mail Hose Mail Fittings Mail UHP Mail



Flat Face Series

- *FF-GP* Standard Duty Flat Face
- FF-HPG High Pressure Flat Face / Grey Nickel Plating
- FF-HP-SS 316 SS, High Pressure Flat Face
- FFK Connectable Under Pressure Nipple
- F-UHP6 10,000 PSI Flat Face
- FF-71 High Pressure Flat Face / Large Body Design
- **F-UHP7** 10,000 PSI Flat Face / DNP Profile

Flat Face Screw Type Series

- PVT4 High Pressure, Fine Thread / DNP Profile
- **PVT4-SL** High Pressure, Fine Thread with Pin Lock / DNP Profile
- **PVT4-SS** 316SS, High Pressure / DNP Profile
- **FSI** High Pressure / Market Interchangeability



rew Type Series

- VFF Medium Pressure / Brass Wing Style
- VFF-HD High Pressure Wing Style *TV1* Large Bore / High Flow
- VV3 Medium Pressure / German Market Interchange
- Medium Pressure
- VS/PVP High Pressure Jack Couplings
- **IPI** 10,000 PSI, 316SS / Brass

oppet/Ball Style Series

- INV General Purpose / ISO A
- INV General Purpose / ISO B
- VS/NV Agriculture Applications
- TNV General Purpose Oil and Gas Applications
- **PPS/PPV** Push/Pull Agriculture Applications
- **PT/PTK** Medium Pressure, High Flow / European Market Interchange
- C 10,000 PSI / Static Application



- S 15,000 & 20,000 PSI, 316SS, Un-Valved Design
- Pressure Washer Couplings, Un-Valved Design / Steel, Brass, 316SS
- 10,000 PSI/15,000 PSI, 316SS, Un-Valved

Multi-Plate Series

- Connect up to four 1/2" hydraulic and/or pneumatic lines
- Connectable Under Pressure
- Special plating to withstand 1,000 hours of salt spray before any visible issues
- Lever & cam actuated locking design to eliminate the brinelling effect typical to inter al and external vibrations
- Keyed system to eliminate wrong connections and crossing fluid lines
- Industries: Oilfield, Construction, Agriculture, Municipality



GCC Series - an RK Voswinkle interchange

- Color Code
- Special plating to withstand 1,000 hours of salt spray before any visible issues
- Spill free screw together
- Connectable under pressure
- Interchange with TCH, Voswinkle and Stauff
- Heavy haul and crane markets

High Pressure Ball Valves

- **BV2** 2-Way Block Style / High Pressure Ball Valves, 1/4" to 2"
- **BV3** 3-Way Block Style / High Pressure Ball Valves, 1/4" to 2"
- **BV2B** 2-Way Round Body / High Pressure Ball Valves 1-1/4", 1-1/2" and 2" • **BV2-MINI** 2-Way High Pressure / 1/4"
- **BV2-ES** 2-Way Excavator Valves
- **BV2-GRS3/GRS6** Pancake Style Valves / SAE 6162, DIN 6164 Patterns
- CV High Pressure Check Valves

Low Pressure Ball Valves

- **BBV** Brass Ball Valves, 600 WOG, Full Port, Nickel Finish / 1/4" to 4"
- SBV Steel Ball Valves, 2,000 PSI, Full Port / 1/4" to 2"
- **SSBV** 316SS Ball Valves, 1,000 PSI, Full Port / 1/4" to 4" • **SSBV** 316SS Ball Valves, 2,000 PSI, Full Port / 1/4" to 4"
- MBBV Brass 1/4" turn Ball Valves, 450 PSI, Nickel Finish

Standard and Heavy Duty Clamps

- Pipe, Tube, Hose Clamps / Polyamide, Polypropylene, Aluminum, Rubber Elastome
- Standard Duty Clamps
- Twin Clamps
- Heavy Duty Clamps
- C-Rail, Rail Nuts, Rubber Bushing Inserts





<u> Hydraulic Hoses</u>

- Bulk Hose and Fittings / OEM Assemblies
- 1SC 1-Wire Braided Hose
- 100R2AT 2-Wire Braided Hose
- 100R16 Compact 2-Wire Braided Hose
- 100R17 1&2-Wire Braided Hose
- *Jack Hose* 2-Wire Braided Hose / 10,000 PSI Static Applications
- *Smoothflex* Compact, Smoothcover 2-Wire Braided Hose
- Freedom 2MT 2-Wire Braided Hose / 1,000,000 Impulse Cycle / MSHA Cover
- Push Lock Hose Textile Braided Hose
- 4SH 4-Spiral Hoses
- **100R13** 4 & 6-Spiral Hoses
- 100R15 4 & 6-Spiral Hoses
- OFW Oilfield Workover Hose
- Freedom 5000/6000 Isobaric 4 & 6-Spiral Hoses / MSHA Cover
- 100R14 Stainless Steel Teflon Hoses
- · Hot Oil Hose
- *Pressure Washer Hose* 3k, 4k, 6k



dustrial Hoses

- Bulk Hose and Cam Locks
- Flex4 Pump Inlet Hoses / Half Bend Radius up to 3" / 100R4
- Bulk Material Discharge 4"
- Hot Air Blower 3" / 150 PSI
- Multipurpose 300 PSI
- Oilfield Suction/Discharge 150 PSI
- **Tank Truck** 150 & 300 PSI • UHMWPE Chemical Corrugated
- Water Suction/Discharge 150 PSI

Hose Fittings

- 200 Series 1-Piece Non-Skive 1SC/100R2AT/100R16/Smoothflex/2MT/100R17/
- 400XF Series 1-Piece Non-Skive 1SC/100R2AT/Fredom6000-5000/100R16/4SH/ **600SF Series** 1-Piece Non-Skive Freedom6000-5000/4SH/OFW/100R13/100R15
- **202** Series 2-Piece Non-Skive (DIN & BSPP) 1SC/100R2AT/100R17/100R16 Smoothflex/Jackhose
- 402 Series 2-Piece Non-Skive (DIN & BSPP) 4SH/Freedom6000-5000
- 800 Series 2-Piece Internal & External Skive (DIN & BSPP) 4SH/100R13/100R15



Ultra High Pressure Valves and Quick Couplings

- NV15/NV20/NV30/NV60 10K,20K,30K,60K 316 SS Needle Valves
- BV10/BV15/BV20 10K, 15K, 20K 2-Way 316 SS Ball Valves • CV15/CV60 15K and 60K Soft and Hard Seat 316 SS Check Valves
- **HPI** 10,000 PSI Gauge Couplings
- HO 10,000 PSI, Un-Valved 316 SS Couplings
- CRS 15,000 & 20,000 PSI, Un-Valved Screw Type Couplings, 316 SS
- 115 UHP 15,000 PSI Couplings
- 116 UHP 20,000 PSI Couplings
- Assortment of Tubing, Tube Fittings and Adapters
- High Pressure tubing and custom tube nipples

Ultra High Pressure Hose

- Waterblast Hoses 1/2" 15,000 PSI / Waterblast Market • Grease Injection Hose 1/2" - 15,000 PSI / Grease Injection for Wireline Market
- VHP-Twin 1/4" Twin Line Thermoplastic Hose / 10,000 PSI w/ a 4 to 1 Safety Factor
- VHP 1/4" Single Thermoplastic Hose / 10,000 PSI w/ a 4 to 1 Safety Factor
- Jack Hose 1/4" & 3/8" 10,000 PSI w/ a 2 to 1 Safety Factor / Static Applications

<u>Ultra High Pressure Fittings</u>

- *WB/GI* 2 -Piece Skive Type for Waterblast and Grease Injection Hose
- VHP 2-Piece Non-Skive for VHP Thermoplastic Hose







