

Push Lock Hose (100R6)



- 1- Synthetic Rubber Tube
- 2- One Braid of Textile
- 3- Synthetic Rubber Cover

Tube: Oil resistant, synthetic rubber

Reinforcement: One braid of textile

Cover: Oil and weather resistant synthetic rubber

Temperature: -40° F / +212° F, Intermittent use up to 250° F

Application: Petroleum based hydraulic fluid, gasoline, water, diesel fuels, lubricating oils, glycol, mineral oils, and more

Termination: 200 series, bite to wire, 1-piece fitting

Key Note: Wide range of standard hydraulic use

Part Number	Hose I.D.		Hose O.D.		Max Working Pressure	Minimum Burst Pressure	Minimum Bend Radius		Weight	Termination
	(in)	(mm)	(in)	(mm)	(psi)	(psi)	(in)	(mm)	(lbs/ft)	Fitting Type
PLH-04	1/4"	.49	12.5	410	1,620	2.6	65	.09	200 series/1-piece	
PLH-05	5/16"	.55	14.0	410	1,620	3.0	75	.10	200 series/1-piece	
PLH-06	3/8"	.62	15.7	410	1,620	3.0	75	.12	200 series/1-piece	
PLH-08	1/2"	.77	19.5	410	1,620	3.9	100	.17	200 series/1-piece	
PLH-10	5/8"	.90	22.9	350	1,420	4.9	125	.21	200 series/1-piece	
PLH-12	3/4"	1.02	26.0	310	1,220	5.9	150	.27	200 series/1-piece	